

27MHZ CB TRANSCEIVER

MODEL K-6124L MK2

6 BANDS 240 CHANNELS NOW !!

**Light weight
Slimline**

4 W of transmit power, 5W max.

Economical



Specifications

General Frequency Coverage

All 240 CB Channels
26.065 to 28.755 MHz

Modulation Mode AM modulation (A3)

Antenna Impedance 50 ohm

Power supply required 12 – 16VDC

Dimensions – (WHD) 124mm x 38mm x 190mm

Weight 1.2Kgs

Receiver Sensitivity

1.0 μ V or better for 10dB S+N/N

Adjacent channel Rejection 60dB (at 10KHz) greater than 70dB (for 20KHz)

Intermediate Frequency 1st IF = 10.695MHz 2nd IF = 455KHz

Audio Output 4.5 Watts max.

Frequency Response 450 – 2500Hz

Cross modulation 45dB or better

Squelch

Adjustable from 1.2 μ V to 1mV

Transmitter Output Power

4 watts nominal, 5 Watts max.

Modulation Capability 80 – 90%

Spurious Radiation 62dB or better

Frequency Tolerance Better than 0.002%

Current Drain (13.8 V supply) 1.3 Amps (no modulation) 2.0 Amps (full modulation)