

# PRESIDENT

## TEDDY ASC

5 years warranty  
PRESIDENT

ASC Automatic Squelch Control



Best price - First Prize **PRESIDENT**

- 5 years warranty • ASC\* (Automatic squelch) • AM/FM
- Priority Channel 9/19 • ANL automatic built-in filter
- Switchable key beep • All European standards...


\*World patented by PRESIDENT

Groupe  
**PRESIDENT**  
ELECTRONICS

1185/09-11 C0260

S.A. Capital 10.000.000 €  
Siège Social / Head Office - France - Route de Sète - BP 100 - 34540 BALARUC  
Site : <http://www.president-electronics.com> - e-mail : [groupe@president-electronics.com](mailto:groupe@president-electronics.com)





1) ON/OFF – VOLUME

2) ASC (Automatic Squelch Control) / SQUELCH

3) CHANNEL SELECTOR ~ BEEP

4) CH9/19 ~ F

5) DISPLAY

6) AM / FM

7) 6 PIN MICROPHONE PLUG

8) PTT

ANL FILTER (Automatic Noise Limiter)

A) DC-POWER TERMINAL (13,2 V)

B) ANTENNA CONNECTOR (SO-239)

C) EXTERNAL SPEAKER JACK (8 Ω, Ø 3,5 mm)

1187/09-11 C0260b

## 1) GENERAL

- Channels : 40
- Modulation modes : AM / FM
- Frequency ranges : from 26.965 MHz to 27.405 MHz
- Antenna impedance : 50 ohms
- Power supply : 13.2 V
- Dimensions (in mm) : 125 (W) x 170 (D) x 45 (H)
- Weight : ~ 0.6 kg
- Accessories supplied : Electret microphone with support, mounting cradle, screws.
- Filter : ANL (Automatic Noise Limiter) built-in

## 2) TRANSMISSION

- Frequency allowance : +/- 200 Hz
- Carrier power : 4 W AM / 4 W FM
- Transmission interference : inferior to 4 nW (- 54 dBm)
- Audio response : 300 Hz to 3 KHz
- Emitted power in the adjacent channel : inferior to 20 μW
- Microphone sensitivity : 7 mV
- Drain : 1,8 A (with modulation)
- Modulated signal dist. : 2 %

# Specifications

## 3) RECEPTION

- Maxi. sensitivity at 20 dB sinad : 0.5 μV - 113 dBm
- Frequency response : 300 Hz to 3 kHz
- Adjacent channel selectivity : 60 dB
- Maximum audio power : 2 W
- Squelch sensitivity : minimum 0.2 μV - 120 dBm  
maximum 1 mV - 47 dBm
- Frequency image rejection rate : 60 dB
- Inter modulation rejection : 48 dB
- Drain : 600 mA nominal  
950 mA maximum



all european standards

