

CB MOBILE MINICOM

- 🔍 LCD
- 🔍 Scan
- 🔍 priority channel 9/19
- 🔍 Squelch, automatic & manual
- 🔍 **Full Multi Norm**



features:

LCD - white symbols on blue background
 RF Gain
 SCAN
 frequency norm selection (DE/PL/EC/EI/UK)
 external speaker connection
 s-meter

dimension : 104 x 24,5 x 108 mm
 weight : ~ 445 g

automatic & manual squelch
 priority channel 9 / 19
 switch AM/FM or UK/EC and scan
 DC 12 V
 Up/Down microphone with signal key

contents : 1 x CB Mobile MiniCom with fixed microphone, 1 x mounting kit, 1 x power supply cable and manual

CB Mobile MiniCom Full Multi Norm

CB3208

DE : 80 FM 26.565 - 27.405 MHz / max. 4 W and 40 AM 26.965 - 27.405 MHz / max. 4 W

EC : 40 FM 26.965 - 27.405 MHz / max. 4 W

EI : 40 FM 26.965 - 27.405 MHz / max. 4 W and 40 AM 26.965 - 27.405 MHz / max. 4 W

PL : 40 FM 26.960 - 27.400 MHz / max. 4 W and 40 AM 26.960 - 27.400 MHz / max. 4 W

UK : 40 FM 26.60125 - 27.99125 MHz / max. 4 W and 40 AM/FM 26.965 - 27.405 MHz / max. 4 W

approved for : AT, BG, CH, CY, CZ, DE, EE, ES, FI, FR, GB, GR, HU, IE,
 IS, IT, LT, LU, LV, MT, NL, PT, PL, RO, SE, SI, SK



CB Mobile MiniCom hp

CB3209

40 channels FM, 4 W / 40 channels AM, 4 W

approved in GR, NO, SE