

Uniden®



PC68LTD

Owner's Manual

Downloaded from www.cbradio.nl



Printed in Vietnam
U01UT408ZZA(0)

CUSTOMER CARE

At Uniden®, we care about you!

If you need assistance, please do NOT return this product to your place of purchase. Our customer care specialists are available to serve you.

Quickly find answers to your questions by:

1. Reading your owner's manual.
2. Visiting our customer support website at www.uniden.com.
3. Calling our customer care specialists at 1-800-658-8068.

Images in this manual may differ slightly from your actual product.

Save your receipt/proof of purchase for warranty.

© 2015. All rights allowed by law are hereby reserved.

Uniden is a registered trademark of Uniden America Corporation.

Bearcat is a registered trademark of Uniden America Corporation.

Features, specifications, and availability of optional accessories are all subject to change without notice.

CONTENTS

CUSTOMER CARE	2
DESCRIPTION	5
EMERGENCY OPERATIONS	5
WHAT'S IN THE BOX.....	5
FRONT VIEW	6
REAR VIEW	7
INSTALLATION.....	7
MOBILE INSTALLATION	7
<i>Mobile Antenna.....</i>	<i>8</i>
<i>Connecting the Power Cords</i>	<i>8</i>
<i>Ground Information</i>	<i>8</i>
USING YOUR PC68LTD	9
TURN PC68LTD ON/OFF	9
CB MODE.....	9
PA MODE.....	10
HI CUT/OFF	10
TO TRANSMIT/RECEIVE	10
MULTI-FUNCTION METER	11
PREVENTIVE MAINTENANCE	11
TROUBLESHOOTING	11
SPECIFICATIONS.....	12
RADIO CODE DEFINITIONS	13
10-CODES.....	13
FCC PART 15 INFORMATION	15
ONE-YEAR EXTENDED WARRANTY	16

DESCRIPTION

Your Uniden PC68LTD represents the highest quality communications device designed for use in the Citizens Band Radio Service. It will operate on any of the 40 AM frequencies authorized by the Federal Communications Commission (FCC).

The Citizens Band Radio Service is under the jurisdiction of the Federal Communications Commission (FCC). Any adjustments or alterations which would alter the performance of the transceiver's original FCC type acceptance, or which would change the frequency determining method, are strictly prohibited. Replacement or substitution of crystal, transistors, ICs, regulator diodes, or any other part of a unique nature, with parts other than those recommend by Uniden, may cause violations of the technical regulations in Part 95 of the FCC Rules or in violation of type acceptance requirements in Part 2 of the rules.

EMERGENCY OPERATIONS

1. Set the switch to CH9 or turn Channel Selector knob to Channel 9.
2. Press PTT switch on microphone and speak clearly.
3. If there is no response, select an active channel and ask that party to RELAY YOUR EMERGENCY BROADCAST ON CHANNEL 9.

All channels, except Channel 9 may be used for normal communication. Channel 9 is reserved by the FCC for emergency communications involving the immediate safety of individuals or protection of property. Channel 9 may also be used to render assistance to a motorist.

This is an FCC rule and applies to all operators of CB radios.

WHAT'S IN THE BOX


Carefully unpack your PC68LTD and check the contents against this list:

- PC68LTD CB 2-way mobile radio
- Microphone
- Mounting Bracket Kit
- DC Power Cord
- Reference Guide
- Part 95 Subpart D (FCC Rules)

If any items are missing or damaged, contact our Customer Care Line immediately at 1-800-658-8068.

Never use damaged products!


FRONT VIEW



Item	Definition
1	Function Meter: Measures RF and S signal strength.
2	NB/ANL/ANL/OFF: Reduces external noise and interference from vehicle ignition systems. Select OFF to turn off this function.
3	CB/PA: Selects the PA (Public Address) or CB (Citizens Band). Do not use PA function unless an external speaker is connected.
4	BRT/DIM: Adjusts the brightness of LED Channel Display and RF Signal Meter.
5	CH9/OFF: Instantly tunes to emergency CB Channel 9. Turn off to resume normal channel operations.
6	HI CUT/OFF: When turned on, cuts high audio frequencies.
7	RX/TX Indicator: Red-transmitting; green-receiving.
8	CH 9 Indicator: Red-Channel 9 switch is on.
9	Channel Display: Displays current channel selection.
10	Channel Knob: Selects transmission and reception channels.
11	MIC GAIN: Adjusts microphone sensitivity.
12	RF GAIN: Improves reception in strong signal areas.
13	SQUELCH: Reduces background noise when there is no incoming signal.
14	On/Off - Volume. Turns the radio on or off and adjusts the speaker volume.

Item	Definition
15	Microphone Jack

REAR VIEW



Item	Definition
16	Antenna Jack
17	PA SP: Connects optional external 8-ohm, 4-watt speaker for use as a public address system. To prevent acoustic feedback, separate the microphone from the speaker when operating the PA at high output levels.
18	EXT. SP: Connects an 8-ohm 4-watt speaker to remotely monitor the receiver. When the external speaker is plugged in, the internal speaker is off.
19	POWER: Connects DC power to transceiver.

INSTALLATION

MOBILE INSTALLATION

Plan the location of the transceiver and microphone bracket before beginning installation.

1. Select a location that is convenient for operating the radio but does not interfere with the driver or passenger.
2. Install bracket with self-tapping screws provided.
3. Connect power cords (see page 8).
4. Attach the microphone bracket to side of the radio.

5. Attach radio to bracket.

Mobile Antenna

WARNING! The antenna used for this radio must be installed at least 17.4 inches (44 cm) away from all persons. The antenna must not be collocated or used with any other antenna or transmitter.

CAUTION: Never operate your radio with no antenna or with a damaged antenna cable. This can damage the radio.

You must purchase an antenna to operate this radio. Because the maximum power output of the transmitter is limited by the FCC, the quality of your antenna is very important. To achieve the maximum transmission distance, Uniden strongly recommends that you install only a high quality antenna. You have just purchased a superior transceiver - don't diminish its performance by installing an inferior antenna.

Only a properly matched antenna system will allow maximum power transfer from the 50 ohm transmission line to the radiating element. Your Uniden dealer is qualified to help you select the proper antenna for your requirements. A whip style antenna may be used for automobile installation.

A short 'loaded' whip antenna is easier to install on an automobile, but its efficiency is less than that of a full quarter-wave whip antenna.

Connecting the Power Cords

Uniden recommends connecting the power lead to the Ignition Switch Accessory Terminal. This way, the transceiver is automatically turned off when the ignition switch is turned off.

As an alternative, the power cord may be connected to an available terminal on the fuse block or to a point in the wiring harness. However, caution must be taken to prevent a short circuit. If in doubt, contact your vehicle dealer for information.


Ground Information

This transceiver may be installed and used in any 12-volt DC negative ground system vehicle.

Negative Ground System

With a negative ground system, the negative (-) battery terminal is usually connected to the vehicle motor block.

Connect the red DC power cord from the transceiver to the positive (+) battery terminal or other convenient point. Then connect the black power cord to the vehicle chassis or negative (-) battery terminal.



USING YOUR PC68LTD

TURN PC68LTD ON/OFF

Turn the **VOLUME** knob clockwise until the unit turns on and the display backlight turns on.

Turn the **VOLUME** knob counter-clockwise to turn the unit off.

CB MODE

Be sure that the power source, antenna, and microphone are properly connected before proceeding.

1. Turn unit on. Set volume to a comfortable level.
2. Set switch to **CB**.
3. Turn the CH knob to select a CB channel.
4. Set noise limitations switch to **NB/ANL**.
5. Adjust squelch.
 - Turn **SQUELCH** knob fully clockwise so only strong signals can get through.
 - Turn **SQUELCH** knob fully counterclockwise until you hear a hiss. Everything gets through - noise, weak signals, and strong signals
 - Turn **SQUELCH** knob clockwise until the hiss stops. Only clearer signals get through.

Set SQUELCH only when the radio is not receiving a strong signal.

6. Press and hold **PTT** and check the multifunction meter. It will show the RF output power.
7. Turn **RF GAIN** knob to set RF gain sensitivity. Normally, the knob is

turned clockwise to maximum.

8. Turn **MIC GAIN** knob to adjust microphone sensitivity for transmission. Normally, the knob is turned clockwise to maximum.
9. Set the brightness (**BRT** or **DIM**).

PA MODE

Using the PA mode requires an optional speaker.

1. Switch to **PA**.
2. Press and hold **PTT** to speak.
3. Release when finished.

To prevent acoustic feedback, separate the microphone from the speaker when operating the PA at high output levels.

If you are in PA mode but not pressing PTT, the radio receives CB transmissions and transmits them through the PA speaker. You cannot respond to the transmission.

HI CUT/OFF

The Hi Cut function reduces high frequencies. Switch to **HI CUT** to turn off higher frequencies.

TO TRANSMIT/RECEIVE

Perform a voltage Standing Wave Ratio (SWR) measurement prior to using the transmitter. An SWR ratio in excess of 2:1 may damage the transmitter.

Be sure to read and understand Part 95, FCC Rules and Regulations before operating your transmitter.

1. Select a channel.
2. Adjust **MIC GAIN**.
3. When the channel is clear, press the microphone **PTT** and speak.
4. Release PTT when you are finished speaking to listen for the response.

MULTI-FUNCTION METER

RF Meter: Measures RF Output Power for transmitter. To use, set the meter switch at **S/RF**. Press microphone **PTT** switch to read transmitting power.

S-Meter: Measures incoming signal strength. To use, set the meter switch at **S/RF**. The meter swings to indicate signal strength.

i.e. S 3, S 5, S 7 ...

PREVENTIVE MAINTENANCE

Every six months:

- Check the Standing Wave Ratio (SWR).
- Be sure all electrical connections are tight.
- Inspect antenna coaxial cable for wear or breaks in shielding.
- Be sure all screws and mounting hardware are tight.

The PC68LTD is designed to give you years of trouble-free service. There are no user-serviceable parts inside. Except for the fuse in the DC power cord, no maintenance is required.

To replace a blown fuse:

1. Press ends of the fuse holder together. Twist to open. Carefully separate the two pieces.
2. Remove the fuse and inspect. If blown, replace with the same type fuse.

Use only the fuse specified for your PC68LTD. Failure to do so may void your warranty.

TROUBLESHOOTING

In the event of system malfunction, perform the following procedures:

Problem	Suggestion
Unit does not power up	Check ignition key position. Check power cord connections. Check fuse. Check vehicle electrical system.

Problem	Suggestion
No reception	Check microphone connection. Set CB/PA to CB . Check VOLUME and SQUELCH . Check antenna. Check antenna connection. Adjust RF Gain .
Poor Reception	Check VOL and SQ . Adjust RF Gain . Be sure antenna SWR is normal.
No Transmission	Set CB/PA switch to CB . Check microphone connection. Adjust MIC Gain .
Low Transmission	Be sure antenna SWR is normal. Adjust MIC Gain .

If you do not get satisfactory results after performing these checks, call the Uniden Customer Service Center at 1-800-297-1023, 8:00 a.m. to 4:30 p.m. CST, Monday through Friday.

SPECIFICATIONS

GENERAL

Channel:	40
Frequency Range:	26.965 - 27.405 MHz
Frequency Control:	PLL Synthesizer
Antenna Impedance:	50 ohms
Power Input:	13.8VDC
Current Drain	
TX:	AM Full Modulation: 2.2A (max)
RX:	At no signal: 400mA Squelch: 250mA
Operating Temperature:	-22°F to 140°F (-30°C to 60°C)
Accessories:	DC Power Cord Microphone Microphone Hanger Mounting Bracket
Size (W x D x H):	6.3 in. x 6.4 in. x 2.2 in. (without knobs and jacks) (160 mm x 162.5 mm x 55.8 mm)

Weight:	3 Pounds
TRANSMITTER	
Output Power:	4 watts
Emission Type:	6A3
Hum and Noise:	Better than 40 dB
Frequency Tolerance:	±0.002%
Modulation Percentage (Peak):	100%
Spurious Rejection:	-70 dB
Output Impedance:	50 ohm, unbalanced

RECEIVER

Sensitivity at 10 dB S+N/N:	0.5 μV
Sensitivity at 500 mW Audio Output:	0.5 μV
Squelch Threshold:	0.5 μV
Antenna Impedance:	50 ohms
Squelch Tight:	1000 μV
Signal Meter S-9:	100 μV
Audio Output Power (max.):	5 watts
Audio Output (10% Dist.):	4 watts
Adjacent Channel Rejection:	60dB
Image Rejection:	70dB
Internal Speaker Impedance:	16 ohms
External Speaker Impedance:	8 ohms

PUBLIC ADDRESS

Output Power at 10% Distortion:	4 watts
---------------------------------	---------

Specifications shown are typical and subject to change without notice.

RADIO CODE DEFINITIONS

10-CODES

The following list contains common “10-Codes” used by CB radio operators for faster communication and better understanding.

Code	Meaning	Code	Meaning
10-1	Received poorly	10-34	Trouble at this station
10-2	Receiving well	10-35	Confidential information

Code	Meaning	Code	Meaning
10-3	Stop transmitting	10-36	Correct time is
10-4	OK, message received	10-37	Wrecker needed at
10-5	Relay message	10-38	Ambulance needed at
10-6	Busy, stand by	10-39	Your message is delivered
10-7	Out of service, leaving air	10-41	Please turn to channel
10-8	In service, subject to call	10-42	Traffic accident at
10-9	Repeat message	10-43	Traffic tie up at
10-10	Transmission completed, standing by	10-44	I have a message for you
10-11	Talking too rapidly	10-45	All units within range please report
10-12	Visitors present	10-50	Break channel
10-13	Advise Weather/ Road conditions	10-60	What is next message number
10-16	Make pickup at	10-62	Unable to copy, use phone
10-17	Urgent business	10-63	Net directed to
10-18	Anything for us?	10-64	Net clear
10-19	Nothing for you, return to base	10-65	Awaiting your next message/assignment
10-20	My location is	10-67	All units comply
10-21	Call by telephone	10-70	Fire at
10-22	Report in person to	10-71	Proceed with transmission in sequence
10-23	Stand by	10-77	Negative contact
10-24	Completed last assignment	10-81	Reserve hotel room for
10-25	Can you contact	10-82	Reserve room for
10-26	Disregard last information	10-84	My telephone number is
10-27	I am moving to channel	10-85	My address is
10-28	Identify your station	10-91	Talk closer to microphone
10-29	Time is up for contact	10-93	Check my frequency on this channel
10-30	Does not conform to FCC rules	10-94	Please give me a long count

Code	Meaning	Code	Meaning
10-32	I will give you a radio check	10-99	Mission completed, all units secure
10-33	EMERGENCY TRAFFIC	10-200	Police needed at

FCC PART 15 INFORMATION

The antenna used for this radio must be properly installed and maintained and must provide a separation distance of at least 44 cm (17.4 inches) from all persons and must not be collocated or operated in conjunction with any other antenna or transmitter. Never transmit if any person is closer than the specified distance to the antenna.

Note that Uniden does not specify or supply any antenna with this transceiver. While a 0 dBi gain antenna is normal for a typical installation, the above limit applies to any antenna with up to 3 dBi gain.

This device complies with Industry Canada licence-exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

Cet appareil est conforme la norme d'Industrie Canada exempt de licence RSS (s). Son fonctionnement est soumis aux deux conditions suivantes : (1) cet appareil ne peut pas provoquer d'interférences, et (2) cet appareil doit accepter toute interférence, y compris les interférences qui peuvent causer un mauvais fonctionnement de l'appareil.

Tous les changements apportés à cet appareil, s'ils ne sont pas expressément approuvés par Uniden ou toute utilisation de celui-ci d'une autre manière que celle décrite dans ce guide peut annuler votre autorisation de le faire fonctionner.

Un guide d'utilisation en français peut être téléchargé à l'adresse suivante :

<http://www.uniden.com/>.

ONE-YEAR EXTENDED WARRANTY

Important: Evidence of original purchase is required for warranty service.

WARRANTOR: UNIDEN AMERICA CORPORATION (“Uniden”)

ELEMENTS OF WARRANTY: Uniden warrants, for one year, to the original retail owner, this Uniden Product to be free from defects in materials and craftsmanship with only the limitations or exclusions set out below.

WARRANTY DURATION: This warranty to the original user shall terminate and be of no further effect one year after the date of original retail sale. The warranty is invalid if the Product is (A) damaged or not maintained as reasonable or necessary, (B) modified, altered, or used as part of any conversion kits, subassemblies, or any configurations not sold by Uniden, (C) improperly installed, (D) serviced or repaired by someone other than an authorized Uniden service center for a defect or malfunction covered by this warranty, (E) used in any conjunction with equipment or parts or as part of any system not manufactured by Uniden, or (F) installed or programmed by anyone other than as detailed by the owner’s manual for this product.

STATEMENT OF REMEDY: In the event that the product does not conform to this warranty at any time while this warranty is in effect, warrantor will either, at its option, repair or replace the defective unit and return it to you without charge for parts, service, or any other cost (except shipping and handling) incurred by warrantor or its representatives in connection with the performance of this warranty. Warrantor, at its option, may replace the unit with a new or refurbished unit. THE LIMITED WARRANTY SET FORTH ABOVE IS THE SOLE AND ENTIRE WARRANTY PERTAINING TO THE PRODUCT AND IS IN LIEU OF AND EXCLUDES ALL OTHER WARRANTIES OF ANY NATURE WHATSOEVER, WHETHER EXPRESS, IMPLIED OR ARISING BY OPERATION OF LAW, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. THIS WARRANTY DOES NOT COVER OR PROVIDE FOR THE REIMBURSEMENT OR PAYMENT OF INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Some states do not allow this exclusion or limitation of incidental or consequential damages so the above limitation or exclusion may not apply to you.

LEGAL REMEDIES: This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. This warranty is void outside the United States of America.

PROCEDURE FOR OBTAINING PERFORMANCE OF WARRANTY: If, after following the instructions in the owner's manual you are certain that the Product is defective, pack the Product carefully (preferably in its original packaging). The Product should include all parts and accessories originally packaged with the Product. Include evidence of original purchase and a note describing the defect that has caused you to return it. The Product should be shipped freight prepaid, by traceable means, to warrantor at:

Uniden America Corporation

C/O Saddle Creek
743 Henrietta Creek Rd., Suite 100
Roanoke, TX 76262

(800) 297-1023, 8 a.m. to 4:30 p.m., Central, Monday through Friday

